



LED-Arbeitsplatzleuchte

Product-Nr.	120720-01
EAN:	4260556620299
Model:	UNILED II Gelenkarm

Order number:	120720-01
Model:	UNILED II Gelenkarm
Type:	LED adjustable arm light
Illuminant:	SMD LED
Power consumption:	~24 W
Lamp luminous flux:	3514 lm
Lamp luminous efficiency:	146 lm/W
Light distribution:	direct
Light colour:	neutral white (4000 - 4500K)
Connected load:	24V DC \pm 10%
Power supply:	included external PSU 100-240V AC
Connection (connector):	M12 A-type encoded
Connected load PSU:	110-240V AC
Connection PSU:	EURO plug to M12 connector
Degree of protection:	IP40
Class of protection:	III
Glare control:	opal white
Beam angle (optics):	100°
Operating temperature:	-10... +60 °C (14... 140 °F)
Colour rendering (Ra):	>85
Lamps lifetime:	> 60.000 h (L80/B10)
Housing material:	aluminium / plastics
Cover material:	plastic soft
Head width [A]:	548 mm
Length articulated arms:	2x 400 mm
Weight (net):	2250 g (~79 oz)
Gross weight:	3950 g (~139 oz)
Risk group (DIN EN 62471):	free group
Markings:	CE, UKCA
Dimmable:	via optional accessory
Mounting accessories:	included table clamp
Made in:	Germany
Feature:	light colour neutral white, high colour rendering

