




## LED adjustable arm light



<b>Product-Nr.</b>	120910-01
<b>EAN:</b>	4260556624785
<b>Model:</b>	UNILED II Articulated Arm
<b>Order number:</b>	120910-01
<b>Model:</b>	UNILED II Articulated Arm
<b>Type:</b>	LED adjustable arm light
<b>Illuminant:</b>	SMD LED
<b>Power consumption:</b>	~14,5 W
<b>Lamp luminous flux:</b>	2668 lm
<b>Lamp luminous efficiency:</b>	~184 lm/W
<b>Light distribution:</b>	Direct
<b>Light colour:</b>	5700K 3-step MacAdam
<b>Colour rendering (Ra):</b>	>90
<b>Supply voltage:</b>	24V DC ± 10%
<b>Power supply:</b>	Included external PSU 100-240V AC
<b>Connection (connector):</b>	M12 A-coded
<b>Connected load PSU:</b>	100-240V AC
<b>Connection PSU:</b>	EURO plug to M12 connector
<b>Degree of protection:</b>	IP40
<b>Class of protection:</b>	III
<b>Glare control:</b>	opal white
<b>Beam angle (optics):</b>	100°
<b>Operating temperature:</b>	-10 °C - +60 °C (14 °F - 140 °F)
<b>Lamps lifetime:</b>	> 100,000 h (L80/B10)
<b>Housing material:</b>	aluminium / plastics
<b>Cover material:</b>	plastic soft
<b>Head width [A]:</b>	380 mm (~14,96")
<b>Length articulated arms:</b>	1x 400 mm (~15,75"), 1x 250 mm (~9,84")
<b>Weight (net):</b>	2900 g (~102 oz)
<b>Gross weight:</b>	3550 g (~125 oz)
<b>Risk group (DIN EN 62471):</b>	Free group
<b>Markings:</b>	CE, UKCA
<b>Dimmable:</b>	Optional via accessories
<b>Mounting accessories:</b>	Included table clamp
<b>Made in:</b>	Germany
<b>Feature:</b>	mid-level luminaire head width and shortened forearm