



LED-Arbeitsplatzleuchte

Product-Nr.	120910-02
EAN:	4260556624792
Model:	UNILED II Gelenkarm
Order number:	120910-02
Model:	UNILED II Gelenkarm
Type:	LED adjustable arm light
Illuminant:	SMD LED
Power consumption:	~16 W
Lamp luminous flux:	2531 lm
Lamp luminous efficiency:	~155 lm/W
Light distribution:	direct
Light colour:	daylight white (5200 - 5700K)
Connected load:	24V DC \pm 10%
Power supply:	included external PSU 100-240V AC
Connection (connector):	M12 A-type encoded
Connected load PSU:	110-240V AC
Connection PSU:	EURO plug to M12 connector
Degree of protection:	IP40
Class of protection:	III
Glare control:	opal white
Beam angle (optics):	100°
Operating temperature:	-10... +60 °C (14... 140 °F)
Colour rendering (Ra):	>85
Lamps lifetime:	> 60.000 h (L80/B10)
Housing material:	aluminium / plastics
Cover material:	plastic soft
Head width [A]:	380 mm
Length articulated arms:	1x 400 mm, 1x 250 mm
Weight (net):	1900 g (~67 oz)
Gross weight:	3550 g (~125 oz)
Risk group (DIN EN 62471):	free group
Markings:	CE, UKCA
Dimmable:	internal dimmer with memory function
Mounting accessories:	included table clamp
Made in:	Germany
Feature:	dimmable, mid-level luminaire head width and shortened forearm