LED recessed light

Product-Nr.	121011-05
EAN:	4260556625744
Model:	CENALED SPOT Recessed





Order number:	121011-05
Model:	CENALED SPOT Recessed
Type:	LED recessed light
Illuminant:	High Power LED
Power consumption:	~8,5 W
Lamp luminous flux:	1120 lm
Lamp luminous efficiency:	134 lm/W
Light distribution:	Direct
Light colour:	5700K 3-step MacAdam
Colour rendering (Ra):	>80
Supply voltage:	24V DC ± 10%
Connection (connector):	M12 A-coded
Degree of protection:	IP67
Class of protection:	III
Beam angle (optics):	15°
Operating temperature:	14 °F - 122 °F
Lamps lifetime:	> 100.000 h (L90/B10)
Housing material:	aluminium (powder-coated)
Cover material:	tempered glass 4 mm (0,16“), crack-resistant
Height [B] x Width [C]:	Built-in housing: ~3,15“ x ~3,15“, installation depth >~2,36“, aperture ~4,13“ x ~4,13“, ~0,2“ built-up
Weight (net):	~14 oz
Gross weight:	~18 oz
Risk group (DIN EN 62471):	Free group
Markings:	CE, UKCA, ETL Listed (5003529)
Dimmable:	Optional via accessories
Made in:	Germany
Feature:	15° optics for spotlight

Irrtümer, Systemfehler und Änderungen vorbehalten./
Errors and technical changes excepted. 6.10.2026

LED2WORK GmbH | Stuttgarter Straße 13 A | 75179 Pforzheim | Germany
T: +49 7231 44920-00 | info@led2work.com | www.led2work.com |
Shop.led2work.com