



## LED workplace light with gooseneck

|                                   |                                                            |
|-----------------------------------|------------------------------------------------------------|
| <b>Product-Nr.</b>                | 121012-01                                                  |
| <b>EAN:</b>                       | 4260556623719                                              |
| <b>Model:</b>                     | CENALED SPOT Flexible Arm                                  |
| Order number:                     | 121012-01                                                  |
| <b>Model:</b>                     | CENALED SPOT Flexible Arm                                  |
| <b>Type:</b>                      | LED workplace light with gooseneck                         |
| <b>Illuminant:</b>                | High Power LED                                             |
| <b>Power consumption:</b>         | ~8,5 W                                                     |
| <b>Lamp luminous flux:</b>        | 1120 lm                                                    |
| <b>Lamp luminous efficiency:</b>  | 134 lm/W                                                   |
| <b>Light distribution:</b>        | direct                                                     |
| <b>Light colour:</b>              | 5000K 3-step MacAdam                                       |
| <b>Connected load:</b>            | 24V DC $\pm$ 10%                                           |
| <b>Power supply:</b>              | -                                                          |
| <b>Connection (connector):</b>    | Connection cable, oil flex, with open cable ends           |
| <b>Degree of protection:</b>      | IP67                                                       |
| <b>Class of protection:</b>       | III                                                        |
| <b>Beam angle (optics):</b>       | 30°                                                        |
| <b>Operating temperature:</b>     | 14 °F - 122 °F                                             |
| <b>Colour rendering (Ra):</b>     | >80                                                        |
| <b>Lamps lifetime:</b>            | > 100.000 h (L90/B10)                                      |
| <b>Housing material:</b>          | aluminium (powder finished)                                |
| <b>Cover material:</b>            | tempered glass, shatterproof                               |
| <b>Flex arm length [A]:</b>       | 19,69"                                                     |
| <b>base height:</b>               | 59 mm (2,32")                                              |
| <b>Mounting:</b>                  | screw-on base                                              |
| <b>Weight (net):</b>              | ~59 oz                                                     |
| <b>Gross weight:</b>              | ~61 oz                                                     |
| <b>Risk group (DIN EN 62471):</b> | free group                                                 |
| <b>Markings:</b>                  | CE, UKCA, ETL Listed (5003529)                             |
| <b>Dimmable:</b>                  | yes, via push button at the light head, ON/OFF and dimming |
| <b>Mounting accessories:</b>      | magnet holder plate optional                               |
| <b>Made in:</b>                   | Germany                                                    |
| <b>Feature:</b>                   | universal workplace light with high protection degree      |

