



| | |
|-----------------------------------|--|
| Product-Nr. | 121012-03 |
| EAN: | 4260556623733 |
| Model: | CENALED SPOT Articulated Head |
| Order number: | 121012-03 |
| Model: | CENALED SPOT Articulated Head |
| Power consumption: | ~8,5 W |
| Lamp luminous flux: | 1120 lm |
| Lamp luminous efficiency: | 134 lm/W |
| Light distribution: | Direct |
| Light colour: | 5000K 3-step MacAdam |
| Colour rendering (Ra): | >80 |
| Connected load: | 24V DC ± 10% |
| Power supply: | - |
| Connection (connector): | Connection cable, oil flex, with open cable ends |
| Degree of protection: | IP67 |
| Class of protection: | III |
| Beam angle (optics): | 30° |
| Operating temperature: | 14 °F - 122 °F |
| Lamps lifetime: | > 100.000 h (L90/B10) |
| Housing material: | aluminium (powder-finished) |
| Cover material: | ESG 3,8 mm, shatterproof |
| base height: | 59 mm (2,32") |
| Weight (net): | ~16 oz |
| Gross weight: | ~19 oz |
| Risk group (DIN EN 62471): | Free group |
| Markings: | CE, UKCA, ETL Listed (5003529) |
| Dimmable: | Yes, via push button at the light head, ON/OFF and dimming |
| Mounting accessories: | Magnet holder plate optional |
| Made in: | Germany |
| Feature: | handy LED luminaire with high degree of protection |

