


LED-Arbeitsplatzleuchte



Product-Nr.	121012-12
EAN:	4260556623757
Model:	CENALED SPOT Gelenkarm
Order number:	121012-12
Model:	CENALED SPOT Gelenkarm
Type:	LED workplace light with adjustable arm
Illuminant:	High Power LED
Power consumption:	~9 W
Lamp luminous flux:	1120 lm
Lamp luminous efficiency:	134 lm/W
Light distribution:	direct
Light colour:	neutral white (5000K)
Connected load:	100-305V AC \pm 10%, 50-60 Hz
Power supply:	inbuilt
Connection (connector):	connection cable 3 m with plug
Degree of protection:	IP65 / Kopf IP67
Class of protection:	I
Beam angle (optics):	30°
Operating temperature:	-10... +50 °C (14... 122 °F)
Colour rendering (Ra):	>80
Lamps lifetime:	> 60.000 h (L80/B10)
Housing material:	aluminium (powder finished)
Cover material:	safety glass, shatterproof
Length articulated arms:	350 mm / 400 mm
base height:	88 mm (3,46")
Weight (net):	1400 g (~49 oz)
Gross weight:	2600 g (~92 oz)
Risk group (DIN EN 62471):	free group
Markings:	CE, UKCA
Dimmable:	yes, via push button at the luminaire head, ON/OFF and dimming
Mounting accessories:	magnet holder plate optional
Made in:	Germany
Feature:	universal workplace light with high protection degree