




## LED Maschinenleuchte



<b>Product-Nr.</b>	121013-05
<b>EAN:</b>	4260556625768
<b>Model:</b>	CENALED SPOT Einbau
<b>Order number:</b>	121013-05
<b>Model:</b>	CENALED SPOT Einbau
<b>Type:</b>	LED recessed light
<b>Illuminant:</b>	High Power LED
<b>Power consumption:</b>	~8,5 W
<b>Lamp luminous flux:</b>	1120 lm
<b>Lamp luminous efficiency:</b>	134 lm/W
<b>Light distribution:</b>	direct
<b>Light colour:</b>	neutral white (5000K)
<b>Connected load:</b>	24V DC $\pm$ 10%
<b>Connection (connector):</b>	M12 A-coded
<b>Degree of protection:</b>	IP67
<b>Class of protection:</b>	III
<b>Beam angle (optics):</b>	65°
<b>Operating temperature:</b>	-10... +50 °C (14... 122 °F)
<b>Colour rendering (Ra):</b>	>80
<b>Lamps lifetime:</b>	> 60.000 h (L80/B10)
<b>Housing material:</b>	aluminium (powder-coated)
<b>Cover material:</b>	safety glass 4 mm (0,16"), crack-resistant
<b>Height [B] x Width [C]:</b>	installation body: ~80 mm x 80 mm (~3,15" x 3,15"), installation depth >60 mm (>2,36"), cover ~105 mm x 105 mm, ~5 mm (~4,13" x 4,13" x 0,2") built-up
<b>Weight (net):</b>	450 g (~16 oz)
<b>Gross weight:</b>	550 g (~19 oz)
<b>Risk group (DIN EN 62471):</b>	free group
<b>Markings:</b>	CE, UKCA, ETL Listed (5003526)
<b>Dimmable:</b>	optional via accessories
<b>Made in:</b>	Germany
<b>Feature:</b>	65° optics for full flat light
<b>Note:</b>	seal included in delivery; fastening via 4 countersunk bolts M5