

LED system light



Product-Nr.	141004-02
EAN:	4260556623191
Model:	SYSTEMLED TW
Order number:	141004-02
Model:	SYSTEMLED TW
Type:	LED system light
Illuminant:	SMD LED
Total output incl. driver:	~49 W
Power consumption:	~41 W
Lamp luminous flux:	4030 lm (6500K) / 3740 lm (3000K)
Lamp luminous efficiency:	~98 lm/W (6500K) / ~91 lm/W (3000K)
Light distribution:	direct
Light colour:	adjustable (3000... 6500K)
Connected load:	220-240V AC ± 10%, 50-60 Hz
Power supply:	inbuilt
Connection (connector):	Wieland GST18
Degree of protection:	IP40
Class of protection:	I
Glare control:	Prismatic cover
Beam angle (optics):	100°
Operating temperature:	-10 °C - +50 °C (14 °F - 122 °F)
Colour rendering (Ra):	>90/98
Lamps lifetime:	> 60.000 h (L80/B10)
Housing material:	aluminium
Height [B] x Width [C]:	40 mm x 138 mm (~1,57" x ~5,43")
Length [A]:	898 mm (~35,35")
Weight (net):	2550 g (~90 oz)
Gross weight:	3500 g (~123 oz)
Risk group (DIN EN 62471):	free group
Markings:	CE, UKCA
Dimmable:	yes
Mounting accessories:	optional
Made in:	Germany
Feature:	stepless switch of the white light colour, cascadable, dim-mable
cascadable:	yes

