




## LED system light



<b>Product-Nr.</b>	141004-06
<b>EAN:</b>	4260556623207
<b>Model:</b>	SYSTEMLED TW
<b>Order number:</b>	141004-06
<b>Model:</b>	SYSTEMLED TW
<b>Type:</b>	LED system light
<b>Illuminant:</b>	SMD LED
<b>Total output incl. driver:</b>	~69 W
<b>Power consumption:</b>	~66 W
<b>Lamp luminous flux:</b>	6448 lm (6500K) / 5984 lm (3000K)
<b>Lamp luminous efficiency:</b>	~98 lm/W (6500K) / ~91 lm/W (3000K)
<b>Light distribution:</b>	direct
<b>Light colour:</b>	adjustable (3000... 6500K)
<b>Connected load:</b>	220-240V AC $\pm$ 10%, 50-60 Hz
<b>Power supply:</b>	inbuilt
<b>Connection (connector):</b>	Wieland GST18
<b>Degree of protection:</b>	IP40
<b>Class of protection:</b>	I
<b>Glare control:</b>	Prismatic cover
<b>Beam angle (optics):</b>	100°
<b>Operating temperature:</b>	-10 °C - +50 °C (14 °F - 122 °F)
<b>Colour rendering (Ra):</b>	>90/98
<b>Lamps lifetime:</b>	> 60.000 h (L80/B10)
<b>Housing material:</b>	aluminium
<b>Height [B] x Width [C]:</b>	40 mm x 138 mm (~1,57" x ~5,43")
<b>Length [A]:</b>	1342 mm (~52,83")
<b>Weight (net):</b>	3750 g (~132 oz)
<b>Gross weight:</b>	4800 g (~169 oz)
<b>Risk group (DIN EN 62471):</b>	free group
<b>Markings:</b>	CE, UKCA
<b>Dimmable:</b>	yes
<b>Mounting accessories:</b>	optional
<b>Made in:</b>	Germany
<b>Feature:</b>	stepless switch of the white light colour, cascadable, dim-mable
<b>cascadable:</b>	yes