



LED-Systemleuchte



| | |
|--------------------|-------------------------------|
| Product-Nr. | 141014-25 |
| EAN: | 4260556620602 |
| Model: | SYSTEMLED ECO Tageslichtweiss |

| | |
|-----------------------------------|---------------------------------|
| Order number: | 141014-25 |
| Model: | SYSTEMLED ECO Tageslichtweiss |
| Type: | LED system light |
| Illuminant: | SMD LED |
| Total output incl. driver: | ~42 W |
| Power consumption: | ~33 W |
| Lamp luminous flux: | 5008 lm |
| Lamp luminous efficiency: | ~155 lm/W |
| Light distribution: | direct |
| Light colour: | daylight white (5200 - 5700K) |
| Connected load: | 220-240V AC \pm 10%, 50-60 Hz |
| Power supply: | inbuilt |
| Connection (connector): | Wieland GST18 |
| Degree of protection: | IP40 |
| Class of protection: | I |
| Glare control: | opal white |
| Beam angle (optics): | 100° |
| Operating temperature: | -10... +50 °C (14... 122 °F) |
| Colour rendering (Ra): | >85 |
| Lamps lifetime: | > 60.000 h (L80/B10) |
| Housing material: | aluminium |
| Height [B] x Width [C]: | 40 mm x 138 mm (1,57" x 5,43") |
| Length [A]: | 1342 mm (52,83") |
| Weight (net): | 3750 g (~132 oz) |
| Gross weight: | 4800 g (~169 oz) |
| Risk group (DIN EN 62471): | free group |
| Markings: | CE, UKCA |
| Dimmable: | via optional accessory |
| Mounting accessories: | optional |
| Made in: | Germany |
| Feature: | cascadable |