

profiled light with t-slot backsided



Product-Nr.	150314-07
EAN:	4260556626413
Model:	PROFILED AC

Order number:	150314-07
Model:	PROFILED AC
Type:	profiled light with t-slot backsided
Illuminant:	SMD LED

Total output incl. driver:	~14 W
Power consumption:	~11 W

Lamp luminous flux:	1670 lm
Lamp luminous efficiency:	~155 lm/W

Light distribution:	Direct
Light colour:	5700K 3-step MacAdam

Colour rendering (Ra):	>85
Connected load:	120-277V AC ± 10%, 50-60 Hz

Power supply:	Integrated
Connection (connector):	Wieland GST18

Degree of protection:	IP40
Class of protection:	I

Glare control:	Microprisms
Beam angle (optics):	100°

Operating temperature:	-10 °C - +45 °C (14 °F - 113 °F)
Lamps lifetime:	> 100,000 h (L80/B10)

Housing material:	aluminium
Cover material:	plastics

Height [B] x Width [C]:	65 mm x 45 mm (~2,56" x ~1,77")
Length [A]:	500 mm (~19,69")

Weight (net):	1450 g (~51 oz)
Gross weight:	1800 g (~63 oz)

Risk group (DIN EN 62471):	Free group
Markings:	CE, UKCA

Mounting accessories:	Optional
Made in:	Germany

Feature:	universal light
----------	-----------------

