



profiled light with t-slot backsided

| | |
|-----------------------------------|---|
| Product-Nr. | 150714-02 |
| EAN: | 4260556623832 |
| Model: | PROFILED DC |
| Order number: | 150714-02 |
| Model: | PROFILED DC |
| Type: | profiled light with t-slot backsided |
| Illuminant: | SMD LED |
| Power consumption: | ~23 W |
| Lamp luminous flux: | 3674 lm |
| Lamp luminous efficiency: | ~155 lm/W |
| Light distribution: | direct |
| Light colour: | 5600K 3-step MacAdam |
| Connected load: | 24V DC ± 10% |
| Connection (connector): | M12 A-coded |
| Degree of protection: | IP40 |
| Class of protection: | III |
| Glare control: | Microprisms |
| Beam angle (optics): | 100° |
| Operating temperature: | -10 °C - +60 °C (14 °F - 140 °F) |
| Colour rendering (Ra): | >85 |
| Lamps lifetime: | > 100,000 h (L80/B10) |
| Housing material: | aluminium |
| Cover material: | plastics |
| Height [B] x Width [C]: | 65 mm x 45 mm (~2,56" x ~1,77") |
| Length [A]: | 1000 mm (~39,37") |
| Weight (net): | 2140 g (~75 oz) |
| Gross weight: | 2840 g (~100 oz) |
| Risk group (DIN EN 62471): | free group |
| Markings: | CE, UKCA, ETL Listed (5003529) |
| Dimmable: | internal dimmer control |
| Mounting accessories: | optional |
| Made in: | Germany |
| Feature: | with dimming control, universally accepted as workbench |

