



poiled light with t-slot backsided



Abstand d=100 cm

E_{min} = 761 lux
E_{max} = 1041 lux
E_{av} = 428 lux



Product-Nr.	150714-02
EAN:	4260556623832
Model:	PROFILED DC
Order number:	150714-02
Model:	PROFILED DC
Type:	poiled light with t-slot backsided
Illuminant:	SMD LED
Power consumption:	~23 W
Lamp luminous flux:	3674 lm
Lamp luminous efficiency:	~155 lm/W
Light distribution:	direct
Light colour:	5600K 3-step MacAdam
Connected load:	24V DC $\pm$ 10%
Connection (connector):	M12 A-coded
Degree of protection:	IP40
Class of protection:	III
Glare control:	Microprisms
Beam angle (optics):	100°
Operating temperature:	14 °F - 140 °F
Colour rendering (Ra):	>85
Lamps lifetime:	> 100,000 h (L80/B10)
Housing material:	aluminium
Cover material:	plastics
Height [B] x Width [C]:	~2,56" x ~1,77"
Length [A]:	~39,37"
Weight (net):	~75 oz
Gross weight:	~100 oz
Risk group (DIN EN 62471):	free group
Markings:	CE, UKCA, ETL Listed (5003529)
Dimmable:	internal dimmer control
Mounting accessories:	optional
Made in:	Germany
Feature:	with dimming control, universally accepted as workbench

