



## profiled light with t-slot backsided

|                                   |                                        |
|-----------------------------------|----------------------------------------|
| <b>Product-Nr.</b>                | 150814-01                              |
| <b>EAN:</b>                       | 4260556623801                          |
| <b>Model:</b>                     | PROFILED DC                            |
| <b>Order number:</b>              | 150814-01                              |
| <b>Model:</b>                     | PROFILED DC                            |
| <b>Type:</b>                      | profiled light with t-slot backsided   |
| <b>Illuminant:</b>                | SMD LED                                |
| <b>Power consumption:</b>         | ~30 W                                  |
| <b>Lamp luminous flux:</b>        | 4676 lm                                |
| <b>Lamp luminous efficiency:</b>  | ~155 lm/W                              |
| <b>Light distribution:</b>        | direct                                 |
| <b>Light colour:</b>              | 5600K 3-step MacAdam                   |
| <b>Connected load:</b>            | 24V DC $\pm$ 10%                       |
| <b>Connection (connector):</b>    | M12 A-coded                            |
| <b>Degree of protection:</b>      | IP40                                   |
| <b>Class of protection:</b>       | III                                    |
| <b>Glare control:</b>             | Microprisms                            |
| <b>Beam angle (optics):</b>       | 100°                                   |
| <b>Operating temperature:</b>     | 14 °F - 140 °F                         |
| <b>Colour rendering (Ra):</b>     | >85                                    |
| <b>Lamps lifetime:</b>            | > 100,000 h (L80/B10)                  |
| <b>Housing material:</b>          | aluminium                              |
| <b>Cover material:</b>            | plastics                               |
| <b>Height [B] x Width [C]:</b>    | ~2,56" x ~1,77"                        |
| <b>Length [A]:</b>                | ~47,24"                                |
| <b>Weight (net):</b>              | ~79 oz                                 |
| <b>Gross weight:</b>              | ~107 oz                                |
| <b>Risk group (DIN EN 62471):</b> | free group                             |
| <b>Markings:</b>                  | CE, UKCA, ETL Listed (5003529)         |
| <b>Dimmable:</b>                  | optional via accessories               |
| <b>Mounting accessories:</b>      | optional                               |
| <b>Made in:</b>                   | Germany                                |
| <b>Feature:</b>                   | universal lighting and/or system light |

