LED2WORK
INTELLIGENCE IN LIGHT

LED Systemleuchte

Product-Nr.	150814-08
EAN:	4260556626482
Model:	PROFILED AC







Order number:	150814-08
Model:	PROFILED AC
Type:	pofiled light with t-slot backsided
Illuminant:	SMD LED
Total output incl. driver:	~34 W
Power consumption:	~30 W
Lamp luminous flux:	4676 lm
Lamp luminous efficiency:	~155 lm/W
Light distribution:	direct
Light colour:	daylight white (5200 - 5700K)
Connected load:	90-305V AC ± 10%, 50-60 Hz
Power supply:	inbuilt
Connection (connector):	GST18
Degree of protection:	IP40
Class of protection:	I
Glare control:	micro prisms
Beam angle (optics):	100°
Operating temperature:	-10... +45 °C (14... 113 °F)
Colour rendering (Ra):	>85
Lamps lifetime:	> 60.000 h (L80/B10)
Housing material:	aluminium
Cover material:	plastics
Height [B] x Width [C]:	65 mm x 45 mm (2,56“ x 1,77“)
Length [A]:	1200 mm (47,24“)
Weight (net):	2500 g (~88 oz)
Gross weight:	3250 g (~115 oz)
Risk group (DIN EN 62471):	free group
Markings:	CE, UKCA
Dimmable:	internal dimmer control
Mounting accessories:	optional
Made in:	Germany
Feature:	universal light, dimmable

LED2WORK GmbH | Stuttgarter Straße 13 A | 75179 Pforzheim | Germany
T: +49 7231 44920-00 | info@led2work.com | www.led2work.com |
Shop.led2work.com