TUBELED_40 II Integrated 151210-01
TUBELED_40 II Integrated RGB-W 151290-01

LED-Maschinenleuchte

Product-Nr.	151210-01
EAN:	4260556623962
Model:	TUBELED_40 II Integrated

Order number:	151210-01
Model:	TUBELED_40 II Integrated
Type:	LED recessed luminaire
Illuminant:	SMD LED
Power consumption:	~24 W
Lamp luminous flux:	3797 lm
Lamp luminous efficiency:	~155 lm/W
Light distribution:	Light Forming Technolology
Light colour:	daylight white (5200 - 5700K)
Connected load:	24V DC ± 10%
Connection (connector):	M12 A-type encoded
Degree of protection:	IP67/IP69K
Class of protection:	III
Glare control:	diffused safety glass
Beam angle (optics):	100°
Operating temperature:	-30... +60 °C (-22… 140 °F)
Colour rendering (Ra):	> 85
Lamps lifetime:	> 60.000 h (L80/B10)
Housing material:	Aluminium
Cover material:	Safety glass, 4 mm (0,16“)
Height [B] x Width [C]:	32 mm x 74 mm (1,26“ x 2,91“), Cover plate 3 mm (0,12“) externally
Length [A]:	570 mm (22,44“)
Weight (net):	1100 g (~39 oz)
Gross weight:	1350 g (~48 oz)
Risk group (DIN EN 62471):	Free group
Dimmable:	via optional accessory
Made in:	Germany

LED2WORK GmbH | Stuttgarter Straße 13 A | 75179 Pforzheim | Germany
T: +49 7231 44920-00 | info@led2work.com | www.led2work.com |
Shop.led2work.com