



TUBELED_40 II Integrated 152010-01
TUBELED_40 II Integrated RGB-W 152090-01

LED recessed light

Product-Nr.	152090-01
EAN:	4260556624570
Model:	TUBELED_40 II Integrated RGB-W
Order number:	152090-01
Model:	TUBELED_40 II Integrated RGB-W
Type:	LED recessed light
Illuminant:	SMD RGB-W Cluster LED
Power consumption white:	~9.5 W
White lamp luminous flux:	1215 lm
Lamp luminous efficiency:	~126 lm/W
Light colour white:	5000K 3-step MacAdam
Power consumption RED:	~9 W
Lamp luminous flux RED:	240 lm
Power consumption GREEN:	~2.5 W
Lamp luminous flux GREEN:	345 lm
Power consumption BLUE:	~9 W
Lamp luminous flux BLUE:	150 lm
Light distribution:	light forming technology
Connected load:	24 V DC -10 % +7 % (RGB) – 24 V DC ±10 % (W)
Connection (connector):	M12 A-coded
Degree of protection:	IP67/IP69K
Class of protection:	III
Glare control:	diffused safety glass
Beam angle (optics):	100°
Operating temperature:	-22 °F - 140 °F
Colour rendering WHITE (Ra):	>80
Lamps lifetime:	> 100,000 h (L80/B10)
Housing material:	aluminium
Cover material:	tempered glass, shatterproof
Height [B] x Width [C]:	~1,26" x ~3,07", aperture ~0.12" built-up
Length [A]:	~13,39"
Weight (net):	~19 oz
Gross weight:	~25 oz
Risk group (DIN EN 62471):	free group
Markings:	CE, UKCA, ETL Listed (5003529), D mark
Made in:	Germany
Feature:	RGB-W: Illumination and beacon in one light