



LED Signalleuchte

Product-Nr.	152290-01
EAN:	4260556624587
Model:	TUBELED_40 II Integrated RGB-W

Order number:	152290-01
Model:	TUBELED_40 II Integrated RGB-W

Type:	LED surface-mounted light
Illuminant:	SMD RGB-W Cluster LED

Power consumption white: ~19 W

White lamp luminous flux: ~19 W

Lamp luminous efficiency: ~126 lm/W

Light colour white: daylight white (5200 - 5700K)

Power consumption RED: ~18 W

Lamp luminous flux RED: 480 lm

Power consumption GREEN: ~5 W

Lamp luminous flux GREEN: 690 lm

Power consumption BLUE: ~18 W

Lamp luminous flux BLUE: 300 lm

Light distribution: light forming technology

Connected load: 24 V DC -10 % +7 % (RGB) – 24 V DC ±10 % (W)

Connection (connector): M12 A-type encoded

Degree of protection: IP67/IP69K

Class of protection: III

Glare control: diffused safety glass

Beam angle (optics): 100°

Operating temperature: -30... +60 °C (-22... 140 °F)

Colour rendering WHITE (Ra): >80

Lamps lifetime: > 60.000 h (L80/B10)

Housing material: aluminium

Cover material: safety glass, shatterproof

Height [B] x Width [C]: 32 mm x 78 mm (1,26" x 3,07")

Length [A]: 700 mm (27,56")

Weight (net): 1100 g (~39 oz)

Gross weight: 1350 g (~48 oz)

Risk group (DIN EN 62471): free group

Markings: CE, UKCA, ETL Listed (5003529)

Made in: Germany

Feature: RGB-W: Illumination and beacon in one light



TUBELED_40 II Integrated 152210-01
TUBELED_40 II Integrated RGB-W 152290-01