



LED recessed luminaire for machines



Abstand d=100 cm

 $E_{\text{min}} = 748 \text{ lux}$ $E_{\text{max}} = 1069 \text{ lux}$ $E_{\text{min}} = 402 \text{ lux}$ 

Product-Nr.	153010-12
EAN:	4260556625447
Model:	FIELDLED EVO Recessed

Order number:	153010-12
Model:	FIELDLED EVO Recessed
Type:	LED recessed luminaire for machines
Illuminant:	SMD LED
Power consumption:	~19 W
Lamp luminous flux:	3000 lm
Lamp luminous efficiency:	155 lm/W
Light distribution:	direct
Light colour:	5600K 3-step MacAdam
Connected load:	24V DC $\pm$ 10%
Connection (connector):	M12 A-coded, rear side
Degree of protection:	IP67/IP69K
Class of protection:	III
Glare control:	Microprisms
Beam angle (optics):	100°
Operating temperature:	-22 °F - 140 °F
Colour rendering (Ra):	>85
Lamps lifetime:	> 100,000 h (L80/B10)
Housing material:	aluminium
Cover material:	ESG (toughened tempered glass), shatterproof
Height [B] x Width [C]:	~1.18" x ~3.78", frame: ~0.22" x ~5.2"
Length [A]:	~11.02"
Weight (net):	~42 oz
Gross weight:	~47 oz
Risk group (DIN EN 62471):	free group
Markings:	CE, UKCA, ETL Listed (5003529)
Dimmable:	optional via accessories
Made in:	Germany

