LED Maschinenleuchte - Aufbauversion



Product-Nr.	153110-02
EAN:	4260556625461
Model:	FIELDLED EVO Aufbau







Order number:	153110-02
Model:	FIELDLED EVO Aufbau
Type:	LED surface-mounted luminaire for machines
Illuminant:	SMD LED
Power consumption:	~39 W
Lamp luminous flux:	6000 lm
Lamp luminous efficiency:	155 lm/W
Light distribution:	direct
Light colour:	daylight white (5200 - 5700K)
Connected load:	24V DC ± 10%
Degree of protection:	IP67/IP69K
Class of protection:	III
Glare control:	microprism
Beam angle (optics):	100°
Operating temperature:	-30... +60 °C (-22... 140 °F)
Colour rendering (Ra):	> 85
Lamps lifetime:	> 60.000 h (L80/B10)
Housing material:	aluminium
Cover material:	ESG (toughened safety glass), shatterproof
Height [B] x Width [C]:	30 x 96 mm (1,18“ x 3,78“)
Length [A]:	540 mm (21,26“)
Weight (net):	~1900 g (~67 oz)
Gross weight:	~2350 g (~83 oz)
Risk group (DIN EN 62471):	free group
Markings:	CE, UKCA, ETL Listed (5003526)
Dimmable:	via optional accessory
Mounting accessories:	optional; two continuous screw channels for metric screws with thread M5 on the reverse
Made in:	Germany
Note:	Connection Plug connector M12 A-coded, rear side

LED2WORK GmbH | Stuttgarter Straße 13 A | 75179 Pforzheim | Germany
T: +49 7231 44920-00 | info@led2work.com | www.led2work.com |
Shop.led2work.com