



LED Maschinenleuchte - Aufbauversion

Product-Nr. 153510-01

EAN: 4260556625591

Model: FIELDLED EVO Aufbau

Order number: 153510-01

Model: FIELDLED EVO Aufbau

Type: LED surface-mounted luminaire for machines

Illuminant: SMD LED

Power consumption: ~86 W

Lamp luminous flux: 13400 lm

Lamp luminous efficiency: 155 lm/W

Light distribution: direct

Light colour: daylight white (5200 - 5700K)

Connected load: 24V DC \pm 10%

Degree of protection: IP67/IP69K

Class of protection: III

Glare control: microprism

Beam angle (optics): 100°

Operating temperature: -30... +60 °C (-22... 140 °F)

Colour rendering (Ra): >85

Lamps lifetime: > 60.000 h (L80/B10)

Housing material: aluminium

Cover material: ESG (toughened safety glass), shatterproof

Height [B] x Width [C]: 30 x 150 mm (1,18" x 5,91")

Length [A]: 702 mm (27,64")

Weight (net): ~3200 g (~113 oz)

Gross weight: ~4000 g (~141 oz)

Risk group (DIN EN 62471): free group

Markings: CE, UKCA, ETL Listed (5003526)

Dimmable: via optional accessory

Mounting accessories: optional; two continuous screw channels for metric screws with thread M5 on the reverse

Made in: Germany