

LED Maschinenleuchte



| | |
|--------------------|---------------|
| Product-Nr. | 154010-01 |
| EAN: | 4260556625836 |
| Model: | TUBELED_25 |

| | |
|----------------------------|--|
| Order number: | 154010-01 |
| Model: | TUBELED_25 |
| Type: | LED surface-mounted light for machines and systems |
| Illuminant: | SMD LED |
| Power consumption: | ~4,3 W |
| Lamp luminous flux: | 667 lm |
| Lamp luminous efficiency: | 155 lm/W |
| Light distribution: | Light Forming Technology |
| Light colour: | daylight white (5200 - 5700K) |
| Connected load: | 24V DC \pm 10% |
| Connection (connector): | M8 A-type encoded |
| Degree of protection: | IP67 |
| Class of protection: | III |
| Glare control: | diffused safety glass |
| Beam angle (optics): | 100° |
| Operating temperature: | -30... +55 °C (-22... 131 °F) |
| Colour rendering (Ra): | >85 |
| Lamps lifetime: | > 60.000 h (L80/B10) |
| Housing material: | aluminium |
| Cover material: | safety glass, 4 mm (0,16") |
| Height [B] x Width [C]: | ~23 mm x ~28 mm (~0,91" x ~1,1") |
| Length [A]: | 205 mm (8,07") |
| Weight (net): | 200 g (~7 oz) |
| Gross weight: | 300 g (~11 oz) |
| Risk group (DIN EN 62471): | free group |
| Markings: | CE, UKCA, ETL Listed (5003526) |
| Dimmable: | optional via accessories |
| Mounting accessories: | optional |
| Made in: | Germany |
| Feature: | very slim and bright, M8 sensor connector A-type coded |

