




LED surface-mounted light for machines and systems



Abstand d=100 cm

E_{max} = 231 luxE_{min} = 328 luxE_{av} = 123 lux**Product-Nr.** 154210-01**EAN:** 4260556625850**Model:** TUBELED_25

Order number: 154210-01

Model: TUBELED_25

Type: LED surface-mounted light for machines and systems

Illuminant: SMD LED

Power consumption: ~8,6 W

Lamp luminous flux: 1333 lm

Lamp luminous efficiency: 155 lm/W

Light distribution: Light Forming Technology

Light colour: 5700K 3-step MacAdam

Colour rendering (Ra): >85

Supply voltage: 24V DC ± 10%

Connection (connector): M8 A-coded

Degree of protection: IP67

Class of protection: III

Glare control: diffused safety glass

Beam angle (optics): 100°

Operating temperature: -30 °C - +55 °C (-22 °F - 131 °F)

Storage temperature: -30 °C - +80 °C (-22 °F - 176 °F)

Lamps lifetime: > 100,000 h (L80/B10)

Vibration resistance: At 10 to 55 Hz (amplitude 0.35 mm (~0,01"))

Shock resistance: Up to 50 g (~2 oz)

Housing material: aluminium

Cover material: tempered glass, 4 mm (0,16")

Height [B] x Width [C]: ~23 mm x ~28 mm (~0,91" x ~1,1")

Length [A]: 370 mm (~14,57")

Weight (net): 50 g (~2 oz)

Gross weight: 400 g (~14 oz)

Risk group (DIN EN 62471): Free group

Markings: CE, UKCA, ETL Listed (5003529)

Dimmable: Optional via accessories

Mounting accessories: Optional

Made in: Germany

Feature: very slim and bright, M8 sensor connector