

| | |
|---|---|
| **Product-Nr.** | 154310-01 |
| **EAN:** | 4260556625867 |
| **Model:** | TUBELED_25 |








| | |
|---|---|
| Order number: | 154310-01 |
| Model: | TUBELED_25 |
| Illuminant: | SMD LED |
| Power consumption: | ~13 W |
| Lamp luminous flux: | 2015 lm |
| Lamp luminous efficiency: | 155 lm/W |
| Light distribution: | Light Forming Technolology |
| Light colour: | 5700K 3-step MacAdam |
| Colour rendering (Ra): | >85 |
| Supply voltage: | 24V DC ± 10% |
| Connection (connector): | M8 A-coded |
| Degree of protection: | IP67 |
| Class of protection: | III |
| Glare control: | diffused safety glass |
| Beam angle (optics): | 100° |
| Operating temperature: | -22 °F - 131 °F |
| Storage temperature: | -22 °F - 176 °F (-30 °C - +80 °C) |
| Lamps lifetime: | > 100,000 h (L80/B10) |
| Vibration resistance: | At 10 to 55 Hz (amplitude ~0.01“) |
| Shock resistance: | Up to ~2 oz |
| Housing material: | aluminium |
| Cover material: | tempered glass, 4 mm (0,16“) |
| Height [B] x Width [C]: | ~0,91“ x ~1,1“ |
| Length [A]: | ~21,26“ |
| Weight (net): | ~2 oz |
| Gross weight: | ~19 oz |
| Risk group (DIN EN 62471): | Free group |
| Markings: | CE, UKCA, ETL Listed (5003529) |
| Dimmable: | Optional via accessories |
| Mounting accessories: | Optional |
| Made in: | Germany |
| Feature: | very slim and bright, M8 sensor connector |



LED2WORK GmbH | Stuttgarter Straße 13 A | 75179 Pforzheim | Germany
T: +49 7231 44920-00 | info@led2work.com | www.led2work.com |
Shop.led2work.com