


LED surface-mounted light



Product-Nr.	154390-01
EAN:	4260556626154
Model:	TUBELED_25 RGB-W

Order number:	154390-01
Model:	TUBELED_25 RGB-W
Type:	LED surface-mounted light
Illuminant:	SMD RGB-W Cluster LED

Power consumption white: ~14,4 W

White lamp luminous flux: 2304 lm

Lamp luminous efficiency: ~159 lm/W

Light colour white: 5000K 3-step MacAdam

Power consumption RED: ~4,3 W

Lamp luminous flux RED: 276 lm

Power consumption GREEN: ~2,9 W

Lamp luminous flux GREEN: 504 lm

Power consumption BLUE: ~4,3 W

Lamp luminous flux BLUE: 168 lm

Light distribution: direct

Connected load: 24 V DC -10 % +7 % (RGB) – 24 V DC ± 10 % (W)

Connection (connector): M8 B-coded

Degree of protection: IP67

Class of protection: III

Glare control: diffused safety glass

Beam angle (optics): 100°

Operating temperature: -22 °F - 131 °F

Colour rendering WHITE (Ra): >85

Lamps lifetime: > 100,000 h (L80/B10)

Housing material: aluminium

Cover material: tempered glass, shatterproof

Height [B] x Width [C]: ~0,91" x ~1,1"

Length [A]: ~21,26"

Weight (net): ~2 oz

Gross weight: ~19 oz

Risk group (DIN EN 62471): free group



Markings: CE, UKCA, ETL Listed (5003529)

Dimmable: option external, PWM

Mounting accessories: option

Made in: Germany

Feature: RGB-W: Illumination and beacon in one light; connection



Abstand d=100 cm

 E_{min} = 341 lux E_{max} = 479 lux E_{av} = 184 lux