





LED surface-mounted light



Abstand d=100 cm

 $E_{\text{max}} = 341 \text{ lux}$
 $E_{\text{min}} = 479 \text{ lux}$
 $E_{\text{avg}} = 184 \text{ lux}$


Product-Nr.	154390-11
EAN:	4260556626277
Model:	TUBELED_25 RGB-W IO-Link
Order number:	154390-11
Model:	TUBELED_25 RGB-W IO-Link
Type:	LED surface-mounted light
Illuminant:	SMD LED RGB + W
Power consumption white:	~14,4 W
White lamp luminous flux:	2300 lm
Lamp luminous efficiency:	160 lm/W
Light colour white:	5000K 3-step MacAdam
Power consumption RED:	~4,3 W
Lamp luminous flux RED:	276 lm
Power consumption GREEN:	~2,9 W
Lamp luminous flux GREEN:	504 lm
Power consumption BLUE:	~4,3 W
Lamp luminous flux BLUE:	168 lm
Light distribution:	direct
Connected load:	24 V DC -5 / +10% [LEDs], 24 V DC +/- 25% [IO-Link communication]
Maximum power consumption White:	680 mA
Maximum current consumption Colors:	220 mA
Connection (connector):	M8 A-coded
Degree of protection:	IP67
Class of protection:	III
Glare control:	diffused safety glass
Beam angle (optics):	100°
Operating temperature:	-22 °F - 131 °F
Colour rendering WHITE (Ra):	>85
Lamps lifetime:	> 100,000 h (L80/B10)
Housing material:	aluminum
Cover material:	tempered glass
Height [B] x Width [C]:	~0,91" x ~1,1"
Length [A]:	~21,26"
Weight (net):	~2 oz
Gross weight:	~19 oz
Risk group (DIN EN 62471):	free group
Markings:	CE, UKCA
Mounting accessories:	optional
Made in:	Germany
Feature:	Only one light for illumination and signaling, IO-Link