





LED surface-mounted light



Abstand d=100 cm

 $E_{\text{min}} = 445 \text{ lux}$ $E_{\text{mid}} = 618 \text{ lux}$ $E_{\text{max}} = 244 \text{ lux}$ **Product-Nr.** 154490-01**EAN:** 4260556626161**Model:** TUBELED_25 RGB-W

Order number: 154490-01

Model: TUBELED_25 RGB-W**Type:** LED surface-mounted light**Illuminant:** SMD RGB-W Cluster LED**Power consumption white:** ~19,2 W**White lamp luminous flux:** 3072 lm**Lamp luminous efficiency:** ~159 lm/W**Light colour white:** 5000K 3-step MacAdam**Power consumption RED:** ~5,8 W**Lamp luminous flux RED:** 368 lm**Power consumption GREEN:** ~3,8 W**Lamp luminous flux GREEN:** 672 lm**Power consumption BLUE:** ~5,8 W**Lamp luminous flux BLUE:** 224 lm**Light distribution:** direct**Connected load:** 24 V DC -10 % +7 % (RGB) – 24 V DC ± 10 % (W)**Connection (connector):** M8 B-coded**Degree of protection:** IP67**Class of protection:** III**Glare control:** diffused safety glass**Beam angle (optics):** 100°**Operating temperature:** -22 °F - 131 °F**Colour rendering WHITE (Ra):** >85**Lamps lifetime:** > 100,000 h (L80/B10)**Housing material:** aluminium**Cover material:** tempered glass, shatterproof**Height [B] x Width [C]:** ~0,91" x ~1,1"**Length [A]:** ~27,76"**Weight (net):** ~5 oz**Gross weight:** ~26 oz**Risk group (DIN EN 62471):** free group**Markings:** CE, UKCA, ETL Listed (5003529)**Dimmable:** option external, PWM**Mounting accessories:** option**Made in:** Germany**Feature:** RGB-W: Illumination and beacon in one light; connection