

LED system light



Product-Nr. 155110-01

EAN: 4260556627069

Model:

Order number: 155110-01

Type: LED system light

Illuminant: SMD LED

Total output incl. driver: ~41 W

Power consumption: ~36,5 W

Lamp luminous flux: 6500 lm

Lamp luminous efficiency: 184 lm/W

Light distribution: Direct

Light colour: 5700K 3-step MacAdam

Colour rendering (Ra): >90 (typ. 95)

UGR: <22

Connected load: 120-277V AC ± 10%, 50-60 Hz

Power supply: Integrated

Connection (connector): Wieland GST18

Degree of protection: IP40

Class of protection: I

Glare control: Microprisms

Beam angle (optics): 90°

Operating temperature: 14 °F - 122 °F

Storage temperature: -4 °F - 176 °F

Lamps lifetime: > 100,000 h (L80/B10)

Housing material: aluminum and PMMA

Height [B] x Width [C]: ~1,89" x ~5,47"

Length [A]: ~35,35"

Mounting: T-slot rear (8 mm)

Weight (net): ~90 oz

Gross weight: ~120 oz

Risk group (DIN EN 62471): Free group

Markings: CE, UKCA

Dimmable: Optional via accessories

Mounting accessories: Optional

Made in: Germany

Feature: externally dimmable/switchable

