





LED system light



Abstand d=100 cm
 E_{max} = 2774 lux
 E_{min} = 3397 lux
 E_{avg} = 1926 lux



Product-Nr.	155410-01US
EAN:	4260556628516
Model:	SYSTEMLED EVO - POWER Daylight White
Order number:	155410-01US
Model:	SYSTEMLED EVO - POWER Daylight White
Type:	LED system light
Illuminant:	SMD LED
Total output incl. driver:	~80 W
Power consumption:	~73 W
Lamp luminous flux:	13000 lm
Lamp luminous efficiency:	184 lm/W
Light distribution:	Direct
Light colour:	5700K 3-step MacAdam
Colour rendering (Ra):	>90 (typ. 95)
UGR:	<22
Scope of delivery:	1x Wieland GST18 cable to NEMA5
Supply voltage:	120-277V AC ± 10%, 50-60 Hz
Power supply:	Integrated
Connection (connector):	Wieland GST18
Degree of protection:	IP40
Class of protection:	I
Glare control:	Microprisms
Beam angle (optics):	90°
Operating temperature:	14 °F - 122 °F
Lamps lifetime:	> 100,000 h (L80/B10)
Housing material:	aluminum and PMMA
Height [B] x Width [C]:	~1,89" x ~5,47"
Length [A]:	~70,16"
Weight (net):	~168 oz
Gross weight:	~234 oz
Risk group (DIN EN 62471):	Free group
Markings:	CE, UKCA, ETL Listed (5003529)
Dimmable:	Optional via accessories
Mounting accessories:	Optional
Made in:	Germany
Feature:	externally dimmable/switchable