## LED tube luminaire

| | |
|---|---|
| **Product-Nr.** | 158010-02 |
| **EAN:** | 4260556628370 |
| **Model:** | INROLED 50 CleanPro ECO |






| | |
|---|---|
| Order number: | 158010-02 |
| Model: | INROLED 50 CleanPro ECO |
| Type: | LED tube luminaire |
| Illuminant: | SMD LED |
| Power consumption: | ~6,5 W |
| Lamp luminous flux: | 1002 lm |
| Lamp luminous efficiency: | ~155 lm/W |
| Light distribution: | Direct |
| Light colour: | 5700K 3-step MacAdam |
| Colour rendering (Ra): | >85 |
| Supply voltage: | 24V DC ± 10% |
| Connection (connector): | M12 A-coded |
| Number of poles: | 3 |
| Degree of protection: | IP67/IP69K |
| Class of protection: | III |
| Glare control: | opal white |
| Beam angle (optics): | 100° |
| Operating temperature: | -30 °C - +70 °C (-22 °F - 158 °F) |
| Cleaning temperature: | Up to max. +80 °C (+176 °F) (light off) |
| Storage temperature: | -30 °C - +80 °C (-22 °F - 176 °F) |
| Lamps lifetime: | > 100.000 h (L80/B10) |
| Housing material: | Tube – Polycarbonate, matt, shatterproof with Ecolab coating \| Cap/M12 connector – V4A stainless steel |
| impact resistance: | IK09 |
| Height [B] x Width [C]: | Ø 50 mm (~1,97“) |
| Length [A]: | 305 mm (~12,01“) |
| Weight (net): | 560 g (~20 oz) |
| Gross weight: | 705 g (~25 oz) |
| Risk group (DIN EN 62471): | Free group |
| Markings: | CE, UKCA, ETL Listed (5003529) |
| Dimmable: | External PWM < 5 kHz |
| Made in: | Germany |
| Feature: | Suitable for F&B use: Ecolab, NSF, and HACCP certified |



LED2WORK GmbH | Stuttgarter Straße 13 A | 75179 Pforzheim | Germany
T: +49 7231 44920-00 | info@led2work.com | www.led2work.com |
Shop.led2work.com