



Socket



| | |
|--------------------------------------|---|
| Product-Nr. | 200200-11 |
| EAN: | 4260556621975 |
| Model: | Accessory Connection |
| Insulation resistance (MOhm): | > 100 |
| Order number: | 200200-11 |
| Model: | Accessory Connection |
| Type: | Socket |
| Coding: | S-coded |
| Amount: | 1 piece |
| Suitable for: | TUBELED_70 AC, INROLED_50 Ecolab AC |
| Connection type: | screwed |
| Number of S-coded poles: | 3+PE |
| Cable passage: | 8 mm -> 10 mm (~0,31" -> ~0,39") |
| Wire cross-section: | max. 1,50 mm ² |
| Cable box material: | Plastic |
| Material: | Contact carrier: plastic, PA, BK; Coupling: CuZn, nickel-plated; Contacts: metal, CuZn, gold-plated; Cable box: plastic |
| Type: | straight |
| Nominal voltage: | 630V DC |
| Operating voltage: | 220 - 240V AC |
| Current load: | 12 A |
| Ambient temperature: | -40°C -> +80 °C (-40 °F -> 176 °F) |
| Passage resistance (ohms): | < 0,003 |
| Insulation resistance (Ohm): | >= 100 Mio. |
| UL: | No |
| Protection class (mounting): | IP67 |
| Contact carrier material: | Plastic, PA, BK |
| Cover material: | CuZn, nickel-plated |
| Contact material: | Metal, CuZn, gold-plated |
| Weight (net): | 50 g (~2 oz) |
| Gross weight: | 100 g (~4 oz) |
| Markings: | CE |
| Note: | assemblable |