DIN rail switching power supply, 24 V DC, for DIN rail mounting

Product-Nr.	210100-04
EAN:	4260556622057
Model:	Constant Voltage Power Supply



Order number:	210100-04
Model:	Constant Voltage Power Supply
Type:	DIN rail switching power supply, 24 V DC, for DIN rail mounting
Ambient temperature:	-25°C -> +70 °C (-13 °F -> 158 °F)
Nominal output voltage:	24V DC
Max. output power:	480 W
Output current:	20000 mA
Voltage range:	90...264V AC
Input frequency:	47...63 Hz
Max. input current (230 V AC):	2500 mA ± 1%
Max. Input current (115 V AC):	5000 mA ± 1%
Output voltage setting range:	24...28V
Overvoltage protection:	29... 33V DC
Efficiency at full load:	94%
P no:	Not suitable for idle operation
Dimensions (mm):	85,5 mm x 125,2 mm x 128,5 mm (~3,37“ x ~4,93“ x ~5,06“)
Overtemperature protection:	90 °C ± 10 °C
Humidity during operation:	20...95% (non-condensing)
Weight (net):	2600 g (~92 oz)
Gross weight:	2700 g (~95 oz)
Markings:	CE, CB, UKCA, UL508 approved, ITE EN/UL/IEC 60950
Dimmable:	Power supply unit can be used in conjunction with PWM dimmers available from LED2WORK GmbH
Protective devices:	short circuit protection, overload protection, overvoltage protection, overtemperature protection

LED2WORK GmbH | Stuttgarter Straße 13 A | 75179 Pforzheim | Germany
T: +49 7231 44920-00 | info@led2work.com | www.led2work.com |
Shop.led2work.com