



## Zubehörartikel

<b>Product-Nr.</b>	210100-04
<b>EAN:</b>	4260556622057
<b>Model:</b>	Konstantspannungs-Netzteil
<b>Order number:</b>	210100-04
<b>Model:</b>	Konstantspannungs-Netzteil
<b>Type:</b>	DIN rail switching power supply, 24 V DC, for DIN rail mounting
<b>Ambient temperature:</b>	-25°C -> +70 °C (-13 °F -> 158 °F)
<b>Nominal output voltage:</b>	24V DC
<b>Max. output power:</b>	480 W
<b>Output current:</b>	20000 mA
<b>Voltage range:</b>	90...264V AC
<b>Input frequency:</b>	47...63 Hz
<b>Max. input current (230 V AC):</b>	2500 mA ± 1%
<b>Max. Input current (115 V AC):</b>	5000 mA ± 1%
<b>Output voltage setting range:</b>	24...28V
<b>Overvoltage protection:</b>	29... 33V DC
<b>Efficiency at full load:</b>	94%
<b>P no:</b>	Not suitable for idle operation
<b>Dimensions (mm):</b>	85,5 mm x 125,2 mm x 128,5 mm (~3,37" x ~4,93" x ~5,06")
<b>Overtemperature protection:</b>	90 °C ± 10 °C
<b>Humidity during operation:</b>	20...95% (non-condensing)
<b>Weight (net):</b>	2600 g (~92 oz)
<b>Gross weight:</b>	2700 g (~95 oz)
<b>Markings:</b>	CE, CB, UKCA, UL508 approved, ITE EN/UL/IEC 60950
<b>Dimmable:</b>	Power supply unit can be used in conjunction with PWM dimmers available from LED2WORK GmbH
<b>Protective devices:</b>	short circuit protection, overload protection, overvoltage protection, overtemperature protection

