


Zubehörartikel



<b>Product-Nr.</b>	210100-07
<b>EAN:</b>	4260556622088
<b>Model:</b>	Konstantspannungs-Netzteil
<b>Order number:</b>	210100-07
<b>Model:</b>	Konstantspannungs-Netzteil
<b>Type:</b>	IP67 power source, metal housing, input: open ends, output: M12 socket, cable protection: flexible metal protection hose
<b>Cable length:</b>	Input: ~0.3 m (~0.98 ft.) with open ends; output ~0.3 m (~0.98 ft.) with M12-A
<b>Number of poles:</b>	4
<b>Ambient temperature:</b>	-40°C -> +80 °C (-40 °F -> 176 °F)
<b>Nominal output voltage:</b>	24V DC
<b>Max. output power:</b>	100 W (96W)
<b>Output current:</b>	4000 mA
<b>Voltage range:</b>	90...305V AC
<b>Input frequency:</b>	47...63 Hz
<b>Max. input current (230 V AC):</b>	550 mA ± 1%
<b>Max. Input current (115 V AC):</b>	1200 mA ± 1%
<b>Output voltage setting range:</b>	22...27V DC
<b>Overvoltage protection:</b>	28...34V DC
<b>Connection to a light:</b>	M12 socket, A-coded
<b>Efficiency at full load:</b>	93%
<b>P no:</b>	Not suitable for idle operation
<b>Degree of protection:</b>	IP67
<b>Dimensions (mm):</b>	220 mm x 68 mm x 38,8 mm (~8,66" x ~2,68" x ~1,53")
<b>Overtemperature protection:</b>	85 °C ± 10 °C
<b>Humidity during operation:</b>	20...95% (non-condensing)
<b>Weight (net):</b>	1150 g (~41 oz)
<b>Gross weight:</b>	1250 g (~44 oz)
<b>Markings:</b>	active PFC, IP65, IP67, ICC, CB, CE, UL8750
<b>Dimmable:</b>	Power supply unit can be used in conjunction with PWM dimmers available from LED2WORK GmbH
<b>Protective devices:</b>	short circuit protection, overload protection, overvoltage protection, overtemperature protection
<b>Feature:</b>	High degree of protection