Switching power supply with M12 socket and connection via a plug

Product-Nr.	210100-11
EAN:	4260556624891
Model:	Constant Voltage Power Supply



PIN 3 **GND**
PIN 4 **V DC**



Order number:	210100-11
Model:	Constant Voltage Power Supply
Type:	Switching power supply with M12 socket and connection via a plug
Cable length:	0,30 m (~0,98 ft.)
Ambient temperature:	-30°C -> +70 °C (-22 °F -> 158 °F)
Nominal output voltage:	24V DC
Max. output power:	~60 W
Output current:	2500 mA
Voltage range:	90...264V AC
Input frequency:	47...63 Hz
Max. input current (230 V AC):	1000 mA ± 1%
Max. Input current (115 V AC):	1400 mA ± 1%
Output voltage setting range:	22...27V DC
Overvoltage protection:	25,2... 32,4V DC
Connection to a light:	M12 socket, A-coded
Number of poles:	4
Overtemperature protection:	75 °C ± 5 °C
Humidity during operation:	20...90% (non-condensing)
Weight (net):	600 g (~21 oz)
Gross weight:	700 g (~25 oz)
Markings:	CE
Feature:	Connection cable can be disconnected via screw coupling

LED2WORK GmbH | Stuttgarter Straße 13 A | 75179 Pforzheim | Germany
T: +49 7231 44920-00 | info@led2work.com | www.led2work.com |
Shop.led2work.com